

**SFX/4C-TY3-SCR-LSF-WHT**

4 Core TCCA Type 3 Alarm Screened White LSF to BS4737-3.30:2015



Cable Construction	
	4 Cores
Conductor	Tinned Copper Clad Aluminium
Conductor Diameter (mm)	0.20 $\pm 0.008 \times 7$
Stranded Diameter (mm)	0.61
Insulation	
Insulation Thickness (mm)	0.21
Insulation Diameter (mm)	1.00 $\pm 0.100$
Insulation Colours	Red,Black,Blue,Yellow
Drain Wire	
Conductor	Tinned Copper Clad Aluminium
Conductor Diameter (mm)	0.20 $\pm 0.008 \times 7$
Al-PET Shield	$\geq 115\%$
Nylon Rip-Cord	Yellow 210D
Jacket	LSF
Jacket Thickness (mm)	0.50
Overall Diameter (mm)	3.90 $\pm 0.200$
Jacket Colour	White RAL 9003
Sheath Printing	(m)
Reaction to Fire	Eca
Electrical Characteristics	
Max Conductor DC resistance @ 20°C	155Ω/km
Rated Temperature	80°C
Rated Voltage	30V
Insulation Resistance @20°C	$>200 \text{ M}\Omega/\text{km}$