

SFX/DS-7-2-2C-LSZH-BLK

Def Standard 7 x 0.2mm 2 Core TCWB Screened Black LSZH



| | |
|------------------------------------|-------------------------|
| Cable Construction | 2 Cores |
| Conductor | Tinned Copper |
| Conductor Diameter (mm) | 0.19 ±0.008 x 7 |
| AWG | 24 |
| Insulation | PVC |
| Insulation Thickness (mm) | 0.30 |
| Insulation Diameter (mm) | 1.20 ±0.10 |
| Insulation Colours | Red,Blue |
| Mylar Spiral | ≥115% |
| Braid | Tinned Copper |
| Braid Construction | 0.12 ±0.008 x 16 x 8 ±2 |
| Braid Coverage | 80% |
| Nylon Rip-Cord | 210D |
| Jacket | LSZH |
| Jacket Thickness (mm) | 0.60 |
| Overall Diameter (mm) | 3.90 ±0.20 |
| Jacket Colour | Black RAL 9005 |
| Sheath Printing | 7-2-2C (PO) (m) |
| Reaction to Fire | Eca |
| Electrical Characteristics | |
| Max Conductor DC resistance @ 20°C | <39Ω/km |
| Rated Temperature | 70°C |
| Rated Voltage | 300V |