

SFX/OFB1-22-LSZH-PUR

OFB1-22 1pr 22AWG Overall Foil and Braid Screen Purple LSZH (3079A)



Cable Construction	1 Pair
Conductor	Bare Copper
Conductor Diameter (mm)	0.65 ±0.008 x 1
Stranded Diameter (mm)	0.65
Insulation	HDPE
Insulation Thickness (mm)	0.4
Insulation Diameter (mm)	2.50 ±0.10
Insulation Colours	Red, Green
Al-PET Shield	≥115%
Drain Wire	
Conductor	N/A
Conductor Diameter (mm)	N/A
Braid	Tinned Copper
Braid Construction	0.15 ± 0.008 x 96
Braid Coverage	≥65%
Nylon Rip-Cord	150D
Jacket	LSZH
Jacket Thickness (mm)	0.9
Overall Diameter (mm)	8.00 ±0.20
Jacket Colour	Purple RAL 4005
Sheath Printing	OFB1 1x2x22AWG Foil & Braid Screen LSZH RoHS2 (PO) (m)
Reaction to Fire	Eca
Electrical Characteristics	
Max Conductor DC resistance @ 20°C	<53Ω/km
Rated Temperature	70°C
Rated Voltage	600V
Insulation Resistance @20°C	>200MΩ/km