

SFX/OFB2-LSF-GRY

OFB2 2pr 24AWG Overall Foil and Braid Screen 600V Grey LSF (9842)



| | |
|------------------------------------|------------------------------------------------------|
| Cable Construction | 2 Pairs |
| Conductor | Tinned Copper |
| Conductor Diameter (mm) | 0.19 ±0.008 x 8 |
| Stranded Diameter (mm) | 0.6 |
| Insulation | HDPE |
| Insulation Thickness (mm) | 0.55 |
| Insulation Diameter (mm) | 1.83 ±0.10 |
| Insulation Colours | White/Blue,Blue;White/Orange,Orange |
| Al-PET Shield | ≥115% |
| Drain Wire | |
| Conductor | Tinned Copper |
| Conductor Diameter (mm) | 0.19 ±0.008 x 7 |
| Braid | Tinned Copper |
| Braid Construction | 0.11 ±0.008 x 128 ±2 |
| Braid Coverage | ≥90% |
| Nylon Rip-Cord | 150D |
| Jacket | LSF |
| Jacket Thickness (mm) | 0.8 |
| Overall Diameter (mm) | 8.65 ±0.20 |
| Jacket Colour | Grey RAL 7042 |
| Sheath Printing | OFB2 2x2x24AWGFoil & Braid Screen LSF RoHS2 (PO) (m) |
| Reaction to Fire | Eca |
| Electrical Characteristics | |
| Max Conductor DC resistance @ 20°C | <83Ω/km |
| Rated Temperature | 80°C |
| Rated Voltage | 600V |
| Insulation Resistance @20°C | >200MΩ/km |