Securi-Flex
Specialist Cable & Connector Supplies

Tel: 0845 094 0244
Fax: 0845 094 0255
www.securiflex.co.uk
sales@securiflex.co.uk

SFX/4C-TY2-SCR-LSF-WHT

4 Core Type 2 Screened LSF Alarm White to BS4737-3.30:2015

Cable Construction	4 Cores
Conductor	Tinned Copper
Conductor Diameter (mm)	0.19 ±0.008 x 7
Stranded Diameter (mm)	0.58
Insulation	PVC
Insulation Thickness (mm)	0.21
Insulation Diameter (mm)	1.00 ±0.100
Insulation Colours	Red,Black,Blue,Yellow
Drain Wire	
Conductor	Tinned Copper
Conductor Diameter (mm)	0.19 ±0.008 x 7
Al-PET Shield	>=115%
Nylon Rip-Cord	Red 210D
Jacket	LSF
Jacket Thickness (mm)	0.50
Overall Diameter (mm)	3.90 ±0.200
Jacket Colour	White RAL 9003
Sheath Printing	(m)
Reaction to Fire	Eca
Electrical Characteristics	
Max Conductor DC resistance @ 20°C	100Ω/km
Rated Temperature	80°C
Rated Voltage	30V
Insulation Resistance @20°C	>200 MΩ/km

Every care is taken to ensure all information in this publication is correct. No Legal responsibility can be accepted for any inaccuracy.
The company reserves the right to alter or modify the information of this specification without notice. E&OE. Registered in England & Wales, Company No.03758330. VAT Number: 736 5084 24.