

SFX/BC-TY3-PE-BLK

8 Core TCCA Type 3 Alarm Black PE



| Cable Construction | 7 Cores | 1 Core |
|------------------------------------|--|------------------------------|
| Conductor | Tinned Copper Clad Aluminium | Tinned Copper Clad Aluminium |
| Conductor Diameter (mm) | 0.20 ±0.008 x 7 | 0.20 ±0.008 x 7 |
| Stranded Diameter (mm) | 0.61 | 0.61 |
| Insulation | PVC | PVC |
| Insulation Thickness (mm) | 0.21 | 0.30 |
| Insulation Diameter (mm) | 1.00 ±0.100 | 1.20 ±0.100 |
| Insulation Colours | Red,Black,Blue,Yellow,Green,White,Orange | Brown |
| Nylon Rip-Cord | Yellow 210D | |
| Jacket | PE | |
| Jacket Thickness (mm) | 0.50 | |
| Overall Diameter (mm) | 4.20 ±0.200 | |
| Jacket Colour | Black RAL 9005 | |
| Sheath Printing | (m) | |
| Reaction to Fire | Fca | |
| Electrical Characteristics | | |
| Max Conductor DC resistance @ 20°C | 155Ω/km | |
| Rated Temperature | 80°C | |
| Rated Voltage | 30V | |
| Insulation Resistance @20°C | >200 MΩ/km | |