


SFX/TWINAX-463-LSZH-BLU

Twinaxial 463 2 Core 20AWG Overall Foil and Braided Screen Blue LSZH (9463)



Cable Construction	2 Cores
Conductor	Tinned Copper
Conductor Diameter (mm)	0.32 ±0.008 x 7(0.52mm²)
Stranded Diameter (mm)	0.81
Insulation	HDPE
Insulation Thickness (mm)	0.49
Insulation Diameter (mm)	1.95 ±0.10
Insulation Colours	Clear, Blue
Filler	1.3mm PE Strip x 2
Mylar Spiral	>=115%
Drain Wire	
Conductor	Tinned Copper
Conductor Diameter (mm)	0.32 ±0.008 x 7
Braiding Shield	Tinned Copper
Braiding Construction	0.12 ±0.008 x 64 ±2
Braiding Coverage	55% ±5%
Jacket	LSZH
Jacket Thickness (mm)	0.85
Overall Diameter (mm)	6.00 ±0.20
Jacket Colour	Blue RAL 5015
Sheath Printing	Twinaxial 463 2x20AWG Overall Foil and Braided Screen LSZH (PO) (m)
Reaction to Fire	Eca
Electrical Characteristics	
Max Conductor DC resistance @ 20°C	<33.10Ω/km
Rated Temperature	70°C
Rated Voltage	600V
Insulation Resistance @20°C	>200MΩ/km
Standards	CE2014/30/EU, RoHS2 2011/65/EU, LVD 2014/35/EU
Application	Control, instrumentation, RF application and computer systems.