


SFX/TWINAX-207-LSZH-BLK

Twinaxial 207 2 Core 20AWG Overall Foil and Braided Screen Black LSZH (9207)



Cable Construction	1 Core	1 Core
Conductor	Tinned Copper	Bare Copper
Conductor Diameter (mm)	0.32 ±0.008 x 7(0.52mm²)	0.32 ±0.008 x 7(0.52mm²)
Stranded Diameter (mm)	0.81	0.81
Insulation	Solid PE	Solid PE
Insulation Thickness (mm)	0.54	0.54
Insulation Diameter (mm)	2.05 ±0.10	2.05 ±0.10
Insulation Colours	Clear	Clear
Inner Jacket	Tube	
Inner Jacket Thickness (mm)	0.85	
Inner Jacket Diameter (mm)	6.0 ±0.20	
Inner Jacket Colour	Clear	
Al-PET Shield	≥115%	
Braiding Shield	Tinned Copper	
Braiding Construction	0.14 ±0.008 x 24 x 6	
Braiding Coverage	85% ±5%	
Outer Jacket	LSZH	
Outer Jacket Thickness (mm)	1.0	
Overall Diameter (mm)	8.40 ±0.20	
Jacket Colour	Black RAL 9005	
Sheath Printing	Twinaxial 207 2x20AWG Overall Foil and Braided Screen LSZH (PO) (m)	
Reaction to Fire	Eca	
Electrical Characteristics		
Max Conductor DC resistance @ 20°C	<33.10Ω/km	
Rated Temperature	70°C	
Rated Voltage	600V	
Insulation Resistance @20°C	>200MΩ/km	
Standards	CE2014/30/EU, RoHS2 2011/65/EU, LVD 2014/35/EU	
Application	Control, instrumentation, RF application and computer systems.	