


SFX/3105A-LSZH-BLK

SFX/3105A 1pr 22AWG Overall Foil and Braided Screen 600V Black LSZH



Cable Construction	1 Pair
Conductor	Tinned Copper
Stranded Diameter (mm)	0.36
Insulation	FPE
Insulation Thickness (mm)	0.70
Insulation Diameter (mm)	2.15 ±0.10
Insulation Colours	White/Blue, Blue/White
Al-PET Shield	≥115%
Drain Wire	
Conductor	Tinned Copper
Conductor Diameter (mm)	0.24 ±0.008 x 7
Braid	Tinned Copper
Braid Construction	0.11 ±0.008 x 16 x 6
Braid Coverage	≥65%
Jacket	LSZH
Jacket Thickness (mm)	0.80
Overall Diameter (mm)	7.20 ±0.20
Jacket Colour	Black RAL 9005
Sheath Printing	3105A 1 pr 22AWG 600V Overall Foil and Braid Screen LSZH RoHS2 (PO) (m)
Reaction to Fire	Eca
Electrical Characteristics	
Max Conductor DC resistance @ 20°C	<57Ω/km
Rated Temperature	70°C
Rated Voltage	600V
Insulation Resistance @20°C	>200MΩ/km
Standards	CE2014/30/EU, RoHS2 2011/65/EU, LVD 2014/35/EU
Application	For use in industrial communication systems (Modbus RS485).