


SFX/OSP15-LSZH-GRY

OSP15 15pr 24AWG Overall Foil Screen 600V Grey LSZH (9515)



Cable Construction	15 Pairs
Conductor	Tinned Copper
Conductor Diameter (mm)	7 x 0.32
Stranded Diameter (mm)	0.22
Insulation	LSZH
Insulation Thickness (mm)	0.28
Insulation Diameter (mm)	1.15 ±0.10
Insulation Colours	7 pairs of Black with Red,White,Green,Blue,Yellow,Brown,Orange; 6 pairs of Red with White,Green,Blue,Yellow,Brown,Orange; 2 pairs of Green with White,Blue
Al-PET Shield	>=115%
Drain Wire	
Conductor	Tinned Copper
Conductor Diameter (mm)	7 x 0.32
Jacket	LSZH
Jacket Thickness (mm)	0.85
Overall Diameter (mm)	10.50 ±0.30
Jacket Colour	Grey RAL 7042
Sheath Printing	OSP15 15x2x24AWG 600V Overall Foil Screened LSZH RoHS2 (PO) (m)
Reaction to Fire	Eca
Electrical Characteristics	
Max Conductor DC resistance @ 20°C	<79.00Ω/km
Rated Temperature	70°C
Rated Voltage	600V
Insulation Resistance @20°C	>200MΩ/km
Standards	CE2014/30/EU, RoHS2 2011/65/EU, LVD 2014/35/EU
Application	Audio, control, instrumentation, panel wiring and RS232 applications.