


SFX/RG11-LSZH-BLK

RG11 Coaxial 7/0.40 Black LSZH



Cable Construction	
Inner Conductor	Stranded Tinned Copper
Conductor Diameter (mm)	7 x 0.40 ±0.008
Insulation	
Insulation Thickness (mm)	Solid PE 3.00 ±0.01
Insulation Diameter (mm)	7.24 ±0.10
Insulation Colour	White
Braid	
Braid Construction	Copper 0.15 ±0.008 x 8 x 24
Braid Coverage	>95%
Jacket	
Jacket Thickness (mm)	LSZH 1.20 ±0.10
Overall Diameter (mm)	10.30 ±0.20
Jacket Colour	Black RAL 9005
Sheath Printing	RG11 LSZH (PO) (m)
Reaction to Fire	Fca
Electrical Characteristics	
Inner Conductor DC resistance @ 20°C	21.0Ω/km
Outer Conductor DC resistance @ 20°C	7.0Ω/km
Rated Temperature	70°C
Impedance	75Ω ±3Ω
Capacitance	67pF/m
Nominal Velocity Ratio	66%
Compliance and Standards	CE2014/30/EU,RoHS2 2011/65/EU,LVD 2014/35/EU
Application	For satellite, television and CCTV installations.