


SFX/ISP2E-LSF-GRY

ISP2E 2pr 24AWG Individual Foil Screen 600V Grey LSF (9729)



Cable Construction	
	2 Pairs
Conductor	Tinned Copper
Conductor Diameter (mm)	0.19 ±0.008 x 7
Stranded Diameter (mm)	0.60
Insulation	
	FPE
Insulation Thickness (mm)	0.480
Insulation Diameter (mm)	1.60 ±0.10
Insulation Colours	Red,Black;Black,White
Al-PET Shield	≥115% (On each pair)
Drain Wire	Each pair is twisted with Individual drain wire inside it's own Al PET-Shield
Conductor	Tinned Copper
Conductor Diameter (mm)	0.19 ±0.008 x 7
Nylon Rip-Cord	White 210D
Jacket	LSF
Jacket Thickness (mm)	1.0
Overall Diameter (mm)	7.80 ±0.20
Jacket Colour	Grey RAL 7042
Sheath Printing	ISP2E 2x2x24AWG Individually Screened LSF RoHS2 (PO) (m)
Reaction to Fire	Eca
Electrical Characteristics	
Max Conductor DC resistance @ 20°C	<89Ω/km
Rated Temperature	80°C
Rated Voltage	600V
Insulation Resistance @20°C	>200MΩ/km